



Material Safety Data Sheet

Coupling Grease MSDS P/N 6979002050 Rev C

MATERIAL SAFETY DATA SHEET
Review Date: 06/30/2005

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: ALVANIA® CG Grease

MSDS NUMBER: 400906E - 1

PRODUCT CODE(S): 71168, 7116800001, 7116802120, 7116802400, 7116830141, 7116835203

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4427, Houston, TX. 77210-4427

TELEPHONE NUMBERS

Spill Information: (877) 242-7400

Health Information: (877) 504-9351

MSDS Assistance Number: (877) 276-7285

SECTION 2 - PRODUCT / INGREDIENTS

CAS#	Concentration	Ingredients
Industrial Grease Mixture	75 - 89.99 %weight	Highly refined petroleum oils
Mixture	10 - 19.99 %weight	Polymer additives (contains zinc)
Mixture	1 - 4.99 %weight	Lithium grease thickener

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview

Appearance & Odor: Dark brown buttery substance. Mild Hydrocarbon Odor.

Health Hazards: No known immediate health hazards. High-pressure injection under the skin may cause serious damage.

Physical Hazards: No known physical hazards.

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3 Extreme - 4

Inhalation: Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.

Eye Irritation: May be irritating to the eyes causing a burning sensation, redness, swelling and/or blurred vision.

Skin Contact: May be irritating to the skin causing a burning sensation, redness and/or swelling. Release of the material during high-pressure applications may result in injection under the skin causing possible extensive tissue damage which is difficult to heal. Other adverse effects not expected from brief skin contact.

Ingestion: Generally considered to have a low order of acute oral toxicity.

Signs and Symptoms: Irritation as noted above. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

Aggravated Medical Conditions: Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

For additional health information, refer to section 11.

SECTION 4 - FIRST AID MEASURES

Inhalation: If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, and then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye: Flush with water. If irritation occurs, get medical attention. If redness, burning, blurred vision or swelling persists, transport to nearest medical facility for additional treatment.

Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. Have victim rinse mouth out with water, and then drink sips of water to remove taste from mouth. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Note to Physician: In general, emesis induction is unnecessary in high viscosity, low volatility products such as oils and greases.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point [Method]: >480 °F/>248.89 °C

Extinguishing Media: Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO₂) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus. This material is non-flammable.

Unusual Fire Hazards: Material may ignite when preheated.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Protective Measures: May burn although not readily ignitable.

Spill Management: Scoop up excess grease. Clean area with appropriate cleaner.

Reporting: CERCLA: Product is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) petroleum exclusion. Releases to air, land, or water are not reportable under CERCLA (Superfund).

CWA: This product is oil as defined under Section 311 of EPA's Clean Water Act (CWA). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures: Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Handling: Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.

Storage: Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Container Warnings: Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Li-Hydroxystearate ACGIH TLV TWA: 10 mg/m³
Oil mist, mineral ACGIH TLV TWA: 5 mg/m³ STEL: 10 mg/m³
Oil mist, mineral OSHA PEL TWA: 5 mg/m³
Hydrogen sulfide ACGIH - TLV TWA: 10 ppm STEL: 15 ppm
Hydrogen sulfide OSHA - PEL_IS TWA: 10 ppm STEL: 15 ppm
Hydrogen sulfide Elevated Temperatures > 180 Degrees F.

Exposure Controls

Adequate ventilation to control airborne concentrations.

Personal Protection

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation. Information on the selection of eye, skin and respiratory protection for use with this material is provided below.

Eye Protection: Chemical Goggles or Safety glasses with side shields

Skin Protection: Use protective clothing which is chemically resistant to this material. Selection of protective clothing depends on potential exposure conditions and may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by: Neoprene, or Nitrile Rubber

Respiratory Protection: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include: For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator. Self-contained breathing apparatus for use in environments with unknown concentrations or emergency situations.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance & Odor: Dark brown buttery substance. Mild Hydrocarbon Odor.

Substance Chemical Family: Lubricants

Appearance: Dark brown buttery substance.

Drop Point: 360 °F

Flash Point: > 480 °F

Odor: Mild Hydrocarbon Odor.

Physical State: Solid

Solubility (in Water): Insoluble

Specific Gravity: 0.95 - 0.96

Stability: Stable

SECTION 10 - REACTIVITY AND STABILITY

Stability: Material is stable under normal conditions.

Conditions to Avoid: Avoid heat and open flames.

Materials to Avoid: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Aldehydes, Carbon Monoxide, Carbon Dioxide, Hydrogen Sulfide, Ketones and other unidentified organic compounds may be formed upon combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity

Oral LD50 120 mg/kg (Rat) OSHA: Non-Toxic Based on components(s)

Carcinogenicity Classification

Industrial Grease

NTP: No IARC: Not Reviewed ACGIH: No OSHA: No

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Impact Summary: There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA Information: Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

SECTION 14 - TRANSPORT INFORMATION

US Department of Transportation Classification: This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

International Air Transport Association: Not regulated under IATA rules.

International Maritime Organization Classification: Not regulated under International Maritime Organization rules.

SECTION 15 - REGULATORY INFORMATION

Federal Regulatory Status

OSHA Classification: Product is hazardous according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Ozone Depleting Substances (40 CFR 82 Clean Air Act): This material does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances.

Superfund Amendment & Reauthorization Act (SARA) Title III: There are no components in this product on the SARA 302 list.

SARA Hazard Categories (311/312): Immediate Health: YES Delayed Health: NO Fire: NO Pressure: NO Reactivity: NO

SARA Toxic Release Inventory (TRI) (313): There are no components in this product on the SARA 313 list.

Toxic Substances Control Act (TSCA) Status: All component(s) of this material is(are) listed on the EPA/TSCA Inventory of Chemical Substances.

Other Chemical Inventories: Component(s) of this material is (are) listed on the Canadian DSL,

State Regulation

This material is not regulated by California Prop 65, New Jersey Right-to-Know Chemical List or Pennsylvania Right-To-Know Chemical List. However for details on your regulation requirements you should contact the appropriate agency in your state.

SECTION 16 - OTHER INFORMATION

Revision#: 1

Review Date: 06/30/2005

Revision Date: 06/30/2005

Revisions since last change (discussion): This Material Safety Data Sheet (MSDS) has been reviewed to comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-2003). We encourage you to take the opportunity to read the MSDS and review the information contained therein.

SECTION 17 - LABEL INFORMATION

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM TO THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR OTHER RELATED REGULATORY REQUIREMENTS.

PRODUCT CODE(S): 71168, 7116800001, 7116802120, 7116802400, 7116830141, 7116835203

ALVANIA® CG Grease

CAUTION!

MAY CAUSE SKIN AND EYE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE OIL ACNE OR DERMATITIS. HIGH-PRESSURE INJECTION UNDER SKIN MAY CAUSE SERIOUS DAMAGE. The following organs and/or organ systems may be damaged by overexposure to this material and/or its components.

Precautionary Measures: Avoid prolonged or repeated contact with eyes, skin and clothing. Avoid breathing of vapors, fumes, or mist. Use only with adequate ventilation. Wash thoroughly after handling.

First Aid

Inhalation: Move victim to fresh air and provide oxygen if breathing is difficult. Get medical attention. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, and then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye Contact: Flush with water. If irritation occurs, get medical attention. If redness, burning, blurred vision or swelling persists, transport to nearest medical facility for additional treatment. **Ingestion:** Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Have victim rinse mouth out with water, and then drink sips of water to remove taste from mouth.

Fire

In case of fire: Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO₂) to extinguish flames. Do not use a direct stream of water.

Spill or Leak

Scoop up excess grease. Clean area with appropriate cleaner.

Contains: Highly refined petroleum oils, Mixture; Polymer additives (contains zinc), Mixture; Lithium grease thickener, Mixture

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Transportation

US Department of Transportation Classification: This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

Name and Address

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4427

ADMINISTRATIVE INFORMATION

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4427, Houston, TX. 77210-4427

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT: IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF SOPUS PRODUCTS AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF SOPUS PRODUCTS.

44280-29739-100R-10/11/2005

Lovejoy, Inc.
World Headquarters
2655 Wisconsin Avenue
Downers Grove, IL 60515
630-852-0500
630-852-2120 Fax
info@lovejoy-inc.com



www.lovejoy-inc.com

ISO 9001-2002 Certified

P/N 697804 02050